



### Main

Range	Vigirex
Device short name	TA30
Product or component type	Earth leakage current sensor
Device application	Equipment monitoring and control
Range compatibility	Vigirex RH plug-in relay
[Ie] rated operational current	65 A

### Complementary

Current sensor type	A type closed toroid
Network type	AC DC
Network frequency	45...440 Hz
[Ui] rated insulation voltage	1000 V
Transformer ratio	1/1000
[Icw] rated short-time withstand current	100 kA / 0.5 s
Residual short-circuit withstand current	85 kA / 0.5 s conforming to IEC 60947-2
Overvoltage category	IV
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Clip-on Vigirex relay Fixed plain backplate Fixed profiled sheet metal Fixed slotted backplate Clip-on DIN rail
Calorific value	0.98 MJ
Connections - terminals	Screw connection : >= 0.22 mm <sup>2</sup>
Diameter	30 mm (inner)
Cable outer diameter	15 mm : 25 mm <sup>2</sup> (maximum)
Product weight	0.12 kg

Height	82 mm
Width	60 mm
Depth	29 mm

## Environment

IP degree of protection	Connectors : IP20 IP30
Environmental characteristic	Exposure to damp heat not in service conforming to IEC 60068-2-30 : 28 cycles 25...55 °C, RH 95 % Salt mist conforming to IEC 60068-2-52 : Kb/2 Exposure to damp heat in service conforming to IEC 60068-2-56 : 48 hours : category C2
Pollution degree	Level 3 conforming to IEC 60664-1
Ambient air temperature for operation	-35...70 °C
Ambient air temperature for storage	-55...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available <a href="#">Product Environmental Profile</a>
Product end of life instructions	Available <a href="#">End of Life Information</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------